

Hydroxyl Boss Air Purifier

Product Specifications



Hydroxyl Boss Air Purifier

The Boss hydroxyl generator is designed for larger spaces and environments that require professional cleaning (to sanitize and deodorize). This portable unit can be used in large offices, retail, senior living and school spaces, and in industrial applications including restoration and remediation following fire or water damage.

The table below summarizes the minimum treatment area in the absence of ventilation, and the treatment area range under typical operating conditions: 3 air changes per hour, 90% recirculated air, and 9 foot (2.7 m) ceilings. If the treated space contains a high contamination or strong odors, the effective treatment area will be smaller than the range listed below. These guidelines should be adhered to for optimal performance and safety.

Operating Guidlines

Minimum Area (if there is no air circulation	1,850 ft ² [171 m ²]
Treatment Range (ft2)	1,500 - 2,500
Treatment Range (m2)	139 - 232

Specifications

Dimensions (LxWxD)	18.25" x 12.1" x 25.3" (464mm x 308mm x 641mm)
Weight	39lbs [17.7kg]
Voltage	120V @ 60Hz / 230V @ 50Hz
P owe r	230 Watts (max)
Number of Optics	2
Fan Rating	110-230 ft ³ /m [186-390 m ³ /h]
Noise Level	<55 dBA
Filter	Washable filter 9" x 18" x 1" (228.6mm x 457.22mm x 25.4mm)
Shipping Dimensions	22" x 15" x 29.5" (559mm x 381mm x 749mm)
Shipping Weight	44lbs, 20.0kg
Certification	ETL US/Canada, CE, RoHS, REACH
Warranty	2 years covering defects in workmanship or materials, but excluding spare parts and consumables

